



TELESCOPIC ARTICULATED LOADERS

608T ▶ 708T



KEY FEATURES

- ▲ 4-Post Canopy ROPS and FOPS Certified
- ▲ Cabin with Heat and Air Conditioning*
- ▲ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ▲ Inching Pedal
- ▲ Digital Display with Audible and Visual Indicators
- ▲ Differential Lock (Hydraulically Activated Front and Rear)
- ▲ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ▲ Telescopic Lift Arm with Z-Bar Loader Linkage with Mechanical Self-Level
- ▲ Lift Arm Float Detent
- ▲ 3-Speed*
- ▲ Hydraglide™ Ride Control*
- ▲ High-Flow Auxiliary Hydraulics*

*Optional features

TELESCOPIC ARTICULATED LOADERS

608T ▶ 708T

PREVIEW

STANDARD FEATURES

- ▲ 4-Post Canopy ROPS and FOPS Certified
- ▲ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ▲ Hydrostatic 2-Speed Transmission
- ▲ Lift Arm Float Detent
- ▲ Inching Pedal
- ▲ Electronic Hand Throttle
- ▲ Digital Display with Audible and Visual Indicators
- ▲ Steering Column with Tilt and Extension Adjustments
- ▲ Cup Holder
- ▲ Differential Lock (Hydraulically Activated Front and Rear)
- ▲ Oscillating Front Frame
- ▲ Rubber Floormat
- ▲ Power-A-Tach® Attachment Mounting System (EuroStyle, 4-Point & Skid Steer)
- ▲ Adjustable Arm Rest
- ▲ Seven-Way Adjustable Seat
- ▲ 12-Volt Socket in Arm Rest
- ▲ Telescopic Lift Arm with Z-Bar Loader Linkage with Mechanical Self-Level
- ▲ Multi-Function Joystick
- ▲ Lift / Tilt Electronic Lockout Switch
- ▲ Reverse and Brake Tail Lights
- ▲ Master Electrical Disconnect Switch
- ▲ Articulation Locking Bar (conforms to SAEJ276)
- ▲ Horn
- ▲ Side View Mirrors
- ▲ Front, Rear & Boon Worklights

OPTIONAL FEATURES

- ▲ 4-Post Canopy with Front and Rear Windows
- ▲ Cabin with Heat
- ▲ Cabin with Heat and Air Conditioning
- ▲ 3-Speed - 608T 11 / 20 / 30 km/h
708T 8 / 20 / 30 km/h
- ▲ Seven-Way Adjustable Air Suspension Seat with or without Sewn Cushions
- ▲ LED Work Lights
- ▲ Speed Control
- ▲ Back-up Alarm
- ▲ Hydraglide™ Ride Control
- ▲ Rear Auxiliary Hydraulics
- ▲ Additional Set of Front Auxiliary Hydraulics
- ▲ High-Flow Auxiliary Hydraulics
- ▲ Radio (Bluetooth Hands-Free)
- ▲ Rotating Beacon
- ▲ Lockable Tool Box
- ▲ Engine Block Heater
- ▲ Front and Rear 12-Volt Electric Auxiliary
- ▲ License Plate Holder
- ▲ Electric Attachment Control 14-Pin Harness with Switches
- ▲ Rear Hitch - Clevis or Receiver
- ▲ 75 mm Seatbelt

SPECIFICATIONS

		608T	708T
DIMENSIONS	Height to Top of Cab / ROPS	2467 mm	2476 mm
	Width over Tires	1645 mm	1957 mm
	Length with Bucket on Ground	5433 mm	5730 mm
	Shipping Length - No Bucket	4615 mm	4927 mm
	Bucket Hinge Pin Height Retracted	3470 mm	3911 mm
	Bucket Hinge Pin Height Extended	4275 mm	5036 mm
	Maximum Dump Angle at Full Height	45°	45°
	Outer Turning Radius	3840 mm	4030 mm
	Articulation Angle from Center	40°	40°
	CAPACITIES	Static Tipping Load with Bucket Retracted	3012 kg
Static Tipping Load with Bucket Extended		1727 kg	1846 kg
Bucket Breakout		4990 kg	4990 kg
Operating Weight with Bucket		4745 kg	5543 kg
ENGINE	Engine Manufacturer	Yanmar	Deutz
	Model / Number of Cylinders	4TNV98CT / 4	TD 3.6 L / 4
	Gross Power @ 2300 rpm	49 kW	55 kW
	Displacement	3.3 L	3.6 L
HYDRAULICS	Work Hydraulic System Flow	70 L/min	70 L/min
	Drive Hydraulic System Pressure	420 bar	380 bar
	Drive Hydraulic Reservoir Capacity (L)	73.7 L	73.7 L
OTHER	Travel Speeds	11/20 km/h	8/20 km/h
	Battery	12 V	12 V
	Fuel Tank Capacity	77 L	115 L
	Tires	405 / 70 20	405 / 70 20

SPECIFICATIONS ARE PRELIMINARY

Mustang reserves the right to add improvements or make changes in features and specifications at any time without notice or obligation.

Mustang reminds users to read and understand the operator's manual before operating any equipment.

Also, make sure all safety devices and shields are in place and functioning properly.

MUSTANG
eu.mustangmfg.com

Find us on
Facebook

MUSTANG MFG.

MANITOU GROUP
430 rue d l'Aubinière - F- 44150 - ANCENIS, Tel: +33 240091011